

SN/SL 70

2-Wege Passivlautsprecher aus Schiefer • Single Wire

Frequenzgang (+/- 3 dB)	45-25.000 Hz
Impedanz	4 Ohm
Empfindlichkeit	86 dB (1 W / 1 m)
Maximaler Schalldruck	105 dB
Frequenzweiche	impedanzkorrigierte Filter 2. Ordnung
Funktionsprinzip.....	Bassreflex
Tief-Mittelton-System	ein Konus-Langhub-Lautsprecher 145 mm, Aluminium mit Spezialbeschichtung
Mittel-Hochton-System.....	ein Kalotten-Lautsprecher 28 mm
Abmessungen mm (H x B x T)	330 x 190 x 250
Gehäuse	gefertigt aus 15/20 mm starken Naturschieferplatten
Gewicht.....	17,5 kg

Gehäuseausführungen: SN = Naturoberfläche, oder SL = geschliffen und lackiert in allen verfügbaren RAL- und PKW-Farben.

Lautsprecherständer als Zubehör: aus schwarz- oder silbereloxiertem, sandgefülltem Aluminiumrohr (Höhe: 690 mm inkl. Bodenplatte, Gewicht: 11 kg) mit massiver Schieferbodenplatte (234 mm x 300 mm x 40 mm), nivellierbar.

2-way passive loudspeaker • Single Wire

Frequency response (+/- 3 dB)	45-25.000 Hz
Impedance	4 ohms
Sensitivity	86 dB (1 W / 1 m)
Max. acoustic pressure	105 dB
Frequency dividing network	2nd order, impedance corrected filter
Function principle	bass reflex
Bass and mid-range system	one long excursion cone speaker 145 mm alloy cone, special coated
Mid-range and treble-system	one dome tweeter 28 mm
Dimensions mm (H x W x D)	330 x 190 x 250
Cabinet	manufactured of 15/20 mm thick natural slate
Weight	17,5 kg

Cabinet design: SN = natural surface, or SL = polished and lacquered in all RAL and available car colours.

Speaker stand (accessory): black or silver anodized, sand filled aluminium tube (height: 690 mm incl. floor plate, weight: 11 kg) with massive slate floor plate (234 mm x 300 mm x 40 mm), adjustable.



FISCHER & FISCHER

Bahnhofstraße 2
D-57392 Schmallenberg-Bad Fredeburg
Tel.: +49 (0) 29 74-8 34 84
Fax: +49 (0) 29 74-8 34 86

e-mail: info@fischer-fischer.de
Internet: www.fischer-fischer.de



SN/SL 70

Lautsprecherbox aus Naturschiefer
Speaker cabinets made of natural slate



FISCHER & FISCHER

MADE IN GERMANY